



16200 S. Figueroa St., Gardena, Ca 90248  
 Tel: 310-324-8880 Fax: 310-324-4020  
 www.sunpkco.com e-mail: info@sunpkco.co,

7.1.10

## Fluorescent High Bay - HB1 Series

### Features

- \* Ideal for both high bay and low bay applications
- \* Precision formed reflector to achieve maximum light output
- \* Opening on back panel for easy ballast maintenance
- \* Heavy duty sheet metal with powder coating
- \* Total Reflection: 90% nom.
- \* Easy ballast access for field service
- \* Supplied with wire guard or without wire guard
- \* Easy ballast access for field service



With or With Wire Guard



With Occupancy Sensor

### Specifications

Models	Ballast	Input Voltage	Input Power (Nom)	PF	THD	Wire Guard	Occupancy Sensor	Lamps	Dimensions
HB1-4T5	2 x U-2/54T5HO	120~277V	220W	> 0.98	< 10 %	Yes	N/A	F54 T5HO	48.2" x 11.0" x 4.6"
HB1-4T8	2 x U-4/32IS HBF	120~277V	145W	> 0.98	< 10 %	Yes	N/A	F32 T8	48.2" x 11.0" x 4.6"
HB1-4T5N	2 x U-2/54T5HO	120~277V	220W	> 0.98	< 10 %	N/A	N/A	F54 T5HO	48.2" x 10.0" x 3.6"
HB1-4T8N	2 x U-4/32IS HBF	120~277V	145W	> 0.98	< 10 %	N/A	N/A	F32 T8	48.2" x 10.0" x 3.6"
HB1-4T5N-LV	2 x U-2/54T5HO	120~277V	220W	> 0.98	< 10 %	N/A	Yes	F54 T5HO	51.2" x 10.0" x 3.6"